

FRONTSignLED®



Montering (DK)

1. Fastgør skiltet på bilen med de medfølgende beslag og skruer. Benyt et beslag i hver side og to beslag både øverst og nederst.
2. Tilpas skiltets facon til lastbilens krumning - og fug med fugemassen hele vejen rundt om skiltet.
3. Forbind lysskiltet til bilens strømsystem ved at forbinde blå til minus og brun til plus.
Benyt vedlagte gummipakdåse (4) til at tætte ledningsgennemføringen. Husk 2A sikring mod overspænding.

Mounting (EN)

1. Attach the sign to the vehicle with the supplied brackets and screws. Use one bracket on each side and two brackets both at the top and bottom.
2. Adjust the shape of the sign to the curvature of the truck - and seal with the sealant all the way around the sign.
3. Connect the illuminated sign to the vehicle's electrical system by connecting blue to minus and brown to plus.
Use the enclosed rubber stuffing box (4) to seal the cable entry. Remember a 2A fuse against overvoltage.



3. 4. 1. 2.



Rengøring/vedligeholdelse (DK)

Rengør aldrig fronterne med højtryksrensere eller rensesvæsker indeholdende opløsningsmidler. Almindeligt sæbevand med en normal PH-værdi er rigeligt til rengøringen.
Vil man forlænge skiltets levetid, bør man afvaske skiltet lige så ofte, som man rengør resten af køretøjet.

Cleaning/maintenance (EN)

Never clean the fronts with a pressure washer or cleaning fluids containing solvents.
Regular soapy water with an average PH level is sufficient for cleaning.
If you want to extend the life of the sign, the sign should be cleaned as often as the rest of the vehicle.